



Overview of Advantages

- For securing the non-hinge side on the secondary closing edge of swing doors made of wood, metal, PVC or glass
- Hard-wearing synthetic fibre fabric: washable, difficult to ignite B1
- Concealed housing fixing screws
- Fabric profile screws visible
- Housing position easy adjustable (elongated holes)
- Suitable for almost all doors
- Certified and supervised quality (MPA)

Incl. accessories

Universal screws

Tender specification

Planet roller-type finger protector FSR 5000 [Basic] for safeguarding the non-hinge side at the secondary closing edge of swing doors. Roller-type protector that automatically maintains a constant tension. Fixing elements on housing side with oblong holes for re-adjusting the roller protector. Profile made of aluminium. Surface finishes: anodised EV1, anodised stainless steel, powder coated RAL 9016, 9007, 7016 (please select). Cover of synthetic fibre, extended length 260 mm, fire retardant B1 treated, colour black. Standard length 1925 mm (for manually operated doors according to DIN 18101 with BRM 2000). Automatic length 2015 mm (for power operated doors according to DIN EN 16005) or fixed length between 310 mm and 2500 mm. (please select supply length)

Technical data

Material	Housing: aluminium, cloth: Synthetic fibre
Length	min. 310 mm to max. 2500 mm
Can be shortened	no
Draw out length	260 mm

Variants that can be ordered

Order number	Version	Surface	Order placement information
F-5111	Standard length (1925 mm)	silver anodised EV1	
F-5121	Standard length (1925 mm)	RAL 9016	
F-5131	Standard length (1925 mm)	RAL 9007	
F-5141	Standard length (1925 mm)	RAL 7016	
F-5151	Standard length (1925 mm)	Matt anodised stainless steel (INOX)	
F-5191	Standard length (1925 mm)	RAL / EURAS (at choice)*	*chargeable option required: Art. no. 901200 or 901201
F-5112	Automatic length (2015 mm)	silver anodised EV1	
F-5122	Automatic length (2015 mm)	RAL 9016	
F-5132	Automatic length (2015 mm)	RAL 9007	
F-5142	Automatic length (2015 mm)	RAL 7016	
F-5152	Automatic length (2015 mm)	Matt anodised stainless steel (INOX)	
F-5192	Automatic length (2015 mm)	RAL / EURAS (at choice)*	*chargeable option required: Art. no. 901200 or 901201
F-5113	made to measure (per linear meter)	silver anodised EV1	
F-5123	made to measure (per linear meter)	RAL 9016	
F-5133	made to measure (per linear meter)	RAL 9007	
F-5143	made to measure (per linear meter)	RAL 7016	

Features



Door types



F-5153	made to measure (per linear meter)	Matt anodised stainless steel (INOX)	
F-5193	made to measure (per linear meter)	RAL / EURAS (at choice)*	*chargeable option required: Art. no. 901200 or 901201

Suitable options

Order number	Product
901200	Surcharge, for powder coating per colour (RAL K1 classic card) and order, payable once only, other colours on request
901201	Surcharge for anodising per colour (EURAS standard colours) and order, payable once only, other colours on request

Accessories/Individual parts

Order number	Product
901320	Installation aid, adhesive pads Installation aid, with 6 adhesive pads
901322	Hex pin wrench for roller protector Hex pin wrench for roller protector, 2 x 20 x 50 mm
901324	Set of screws for roller protector FSR 5000 [Basic] Screws for roller protector FSR 5000 [Basic], 10 pcs each/type of screw
901300	Planet marking aid Planet marking aid, plastic, black, set incl. pencil