

CareMat B

The pressure-sensitive mat for supervision of people with dementia and disorientation

Product Description

CareMat is used in retirement and nursing homes as well as in hospitals and similar facilities. It is placed beside the patient's bed or by the room door exit. In both cases the CareMat is connected to the in-house nurse call system. As soon as the person leaves the bed or the room he will step onto the CareMat and a signal is triggered via the nurse call system. This allows the personnel on duty to establish at any time of the day or night, when and where a patient got out of bed or is leaving the room. As a result, CareMat contributes to providing assistance immediately, thus significantly reducing the risk of falls or the danger of patient wandering.



Selection chart

CareMat **B** **0** **1** **T** **E868**

■ Dimension code

- A 1100 x 700 mm
- B 700 x 400 mm
- C 1100 x 700 mm, semi-circular
- M 283 x 202 mm, sample

■ Colour code

- 0 Careyellow
- 1 Caregrey

■ Case code

- 1 56 x 38 x 9.6 mm

■ Type code

- E Empty
- C Open cable head
- T Transmitter

■ Transmitter type code

- E868 ELDAT 868.30 MHz
- L869 Lehmann electronic 869.2125 MHz
- T868.8 TeleAlarm® 868.8 MHz

Features

- Dimensions 700 x 400 mm
- Hard-wired and wireless versions
- A robust and reliable alarm sensor
- Hygienic: Easy to clean and resistant to bodily fluids

Content

- 1 Product description
Selection chart
Features
- 2 Model list
Technical specifications
- 3 Technical specifications
CareMat dimensions
Case dimensions
- 4 Product details

CE The EU Declarations of Conformity are available at the following address:
<https://www.bircher.com/en/downloads/>

Model list

Product	Colour	Part number	Description
CareMat	B01E	Careyellow	700 x 400 mm / empty housing
	B11E	Caregrey	
CareMat	B01C	Careyellow	700 x 400 mm / cable
	B11C	Caregrey	
CareMat	B01T E868	Careyellow	700 x 400 mm / ELDAT radio transmitter 868.30 MHz
	B11T E868	Caregrey	
CareMat	B01T L869	Careyellow	700 x 400 mm / Lehmann radio transmitter 869.2125 MHz
	B11T L869	Caregrey	
CareMat	B01T T868.8	Careyellow	700 x 400 mm / TeleAlarm® radio transmitter 868.8 MHz
	B11T T868.8	Caregrey	

Technical Specifications

Characteristics

CareMat General

Dimensions	Surface: 700 x 400 x 9.5 mm / height standard case 1: 14.5 mm
Weight	3.2 kg
Material	Polyurethane PU
Colour	Careyellow / Caregrey
Surface	Nub structure with sloped edges
Person activation weight	Min. 10 kg
Chemical resistance	Water, bodily fluids, commercially available disinfectants, max. 70 % vol. alcohol
Protection class	IP54, dust- and splash-proof
Temperature range	0 to +55 °C

CareMat versions with cable

CareMat B01E / B11E

Connection	This CareMat can be equipped by cable or various transmitters.
------------	--

CareMat B01C / B11C

Cable	Length 3 m, diameter 5.2 ± 0.2 mm, cable colour white
Cable type	4-wire, LiYYv 4 x 0.34 mm ² , wire colours BN/YE/GN/WH, open cable head
Cable as spare part	According to above specifications available, part number 307131
Signal output	Normally open contact (NO)
Admissible capacity	Max. 50 mA at 48 V AC/DC

CareMat wireless versions

CareMat B01T E868 / B11T E868

Radio transmitter	ELDAT, 1 channel, unidirectional
Radio frequency	868.30 MHz, EasyWave® protocol
Radio range	up to 30 m in buildings, dependent on structural building conditions (up to 250 m in free field)
Battery type	1 x CR2032, 3 V Lithium button cell
Runtime; battery	2 years

CareMat B01T L869 / B11T L869


Radio transmitter	Lehmann electronic VarioRec®, 1 channel, unidirectional
Radio frequency	869.2125 MHz, VarioRec® protocol
Radio range	up to 30 m in buildings, dependent on structural building conditions (up to 100 m in free field)
Battery type	1 x CR2032, 3 V Lithium button cell
Runtime; battery	3 years
Battery monitoring	Battery low message

Characteristics


CareMat B01T T868.8 / B11T T868.8

Radio transmitter	TeleAlarm® UPCBA80; Signalling protocol TeleAlarm® NurseCall 8
Radio frequency	868.8 MHz bidirectional
Radio range	up to 30 m in buildings, dependent on structural building conditions (up to 100 m in free field)
Battery type	1x CR2430, 3 V Lithium
Runtime; battery	depending on use up to 2.5 years
Battery monitoring	Battery low message

CareMat Dimensions




Case Dimensions (Standard)




Product Details

Front



Back



Packaging



Find out more about the product online
www.bircher.com

